

CI/SfB | (74.1) | g3 |

Date | October 2016

Supersedes all previous issues

## Sydney Smart II 305 Easy Height Round Front

1.28/0.8 gpf (4.8/3 I) Water Saving Dual Flush High Efficiency Toilet (HET) Two Piece Vitreous China Washdown Toilet









## Sydney Smart II 305 Easy Height Round Front Vitreous China Washdown Toilet 1.28/0.8 gpf (4.8/3 I) **Dual Flush HET**

## Two Piece High Efficiency (HET)



A modern concept close coupled washdown 1.28/0.8 gpf (4.8/3 I) Sydney Smart II 305 Easy Height Round Front dual flush high efficiency toilet (HET) featuring unique two button activation providing substantial water saving compared to other HET or standard toilets and smooth rounded contours for easy cleaning. The closet bowl has been designed with a 12" (305 mm) outlet rough-in. The tank incorporates a high performance outlet valve which has been specially developed with the 305 Round Front bowl to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 l) dual flush system, the toilet is suitable for multi-purpose applications where water conservation is important.

305 Round Front 1.28/0.8 gpf (4.8/3 I) full flush washdown closet bowl with box Closet bowl:

flushing rim.

Floor mounted 12" (305mm) round front outlet connection. Outlet:

Tank: Sydney Smart II Tank - has a free fitting lid and is suitable for domestic and light commercial

applications.

97 lbs (44 kg) Weight:

Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water **Water Control** Valve:

control assembly. Internal overflow only.

The tank is fixed directly to the closet bowl with a robust base fixing system without the need Fixing:

for wall fixing.

The slow closing round front seat is included: Code No. 326201W. Seat:

Colors:

All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Dimensions:

The right is therefore reserved to vary specifications without notice.

Caroma pursues a policy of continuing improvement in design and performance of its products.

Sydney Smart II 350 (480 mm)Easy Height Round Front Code No. Tank LH inlet 302100W 305101W Bowl 140mm (715mm) (415mm) 3/8"  $\Gamma_{14-3/8}$ " (365mm) 250mm (455mm min.) 3/4" (20mm) appro IAPMO R&T (860mm) 33-7/8" 7-1/2" **Note:** All height dimensions to underside of closet bowl. Make allowance for bedding. Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking. Center Line of Outlet (305mm)