Elkay SwirlFlo Single Fountain Non-Filtered Non-Refrigerated

Model EDFPBW114C

PRODUCT SPECIFICATIONS

Elkay SwirlFlo® Single Fountain Non-Filtered Non-Refrigerated, Stainless. Furnished with Flexi-Guard ® Safety Bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 1 station(s). Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

Finish:	Stainless Steel
Power:	No Electrical Required
Bubbler Style:	Flexi-Guard ® Safety Bubbler
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Option:	Non-refrigerated
Dimensions (L x W x H):	19-3/4" x 19" x 21-15/16"
Approx. Shipping Weight:	22 lbs.
Installation Location:	Indoor
No. of Stations Served:	1

Special Note: Requires In-Wall Carrier MPW101 (sold separately)

 Mechanically-Activated bubbler continues to supply water in event of service disruptions.



AMERICAN PRIDE. A LIFETIME TRADITION.

Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



Included with Product: Fountain with Back Plate,

PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 Buy American Act NSF/ANSI 61 & 372 (lead free)





Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF)

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty. Warranty (PDF)

OPTIONAL ACCESSORIES

EWF1/2 - WaterSentry VII Filter Kit (Coolers + Fountains)	
MPW101 - Accessory - In Wall Carrier (Single) for EDFP210,	
EDFP214, EDFPB114, EDFPBW114, EHW214 models	
AP99 - Elkay Access Panel 9" x 9" x 6"	
97446C - Accessory - Bubbler Kit Vandal-Resistant	

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



Model EDFPBW114C OPERATION OF QUICK CONNECT FITTINGS **INSTALLER NOTE** 1/4" O.D. TUBE WATER INLET 3/8" O.D. TUBE CONNECT COLD WATER SUPPLY This drinking fountain is furnished with a bubbler **BUILDING WATER** SIMPLY PUSH IN TUBE TO ATTACH TUBE IS SECURED IN POSITION PUSH IN COLLET TO RELEASE TUBE and valve including all connecting fittings which TO COOLER are manufactured of completely lead free material. • + 4407 Shut off valve (not furnished) to accept 3/8" O.D. 777/ 777/ unplated copper tube. ㅁ PUSHING TUBE IN BEFORE PULLING IT OUT HELPS TO RELEASE TUBE NOTE: WATERFLOR SERVICE STOP (NOT FURNISHED) DIRECTION 19-3/4" 18-3/8 (502mm) (467mm) (16mm) ORIFICE 1-1/4" I.P.S. WASTE (LEFT OR RIGHT). WASTE IS SHOWN IN WALL, BUT MAY TO RIM -1-5/8" (41mm) 21-15/16" (557mm) BE BEHIND WALL 28-3/4" (730mm) WASTE OPTIONAL ACCESS PANEL AND FRAMING NOT SHOWN 9" SQ 33-15/16" (863mm) (229mm) 21-1/2" (546mm) SUPPLY RECOMMENDED SHUT OFF 3/8" I.P.S. SUPPLY 16-1/2" AP99 ACCESS PANEL 27" (686mm) (LEFT OR RIGHT) (419mm) WASTE ELBOW, BY OTHERS EXTENSION AND TRAP BY OTHERS (OPTIONAL) NOTE REQUIREMENT 13-3/4" (349mm) INSTALLATION CAN BE MADE THRU OPTIONAL FRONT ACCESS PANEL OR FROM REAR ACCESS FINISHED FLOOR SUPPORT PREPARATION NOTE (406mm) WALL PLATE MUST BE SUPPORTED SECURELY. ADD FIXTURE SUPPORT CARRIER IF WALL WILL NOT PROVIDE ADEQUATE SUPPORT. 9-3/4" (248mm) (203mm) 5-1/4" (133mm) 5-1/4" (133mm) 1-1/4" 1/4" (8mm) DIA. HOLES FOR MOUNTING PLATE TO WALL (32mm)BACK PANEL SURFACE MOUNTING 1-1/4" (32mm) I.P.S. WASTE (LEFT OR RIGHT) WASTE IS SHOWN IN WALL, BUT MAY BE BEHIND WALL. 3/8" (10mm) DIA. HOLES FOR MOUNTING PLATE TO WALL (10) SUPPLY 3/8" I.P.S. LEFT OR RIGHT SIDE 7-7/8" (200mm) 43-5/8" (1108mm) 烘光 (203mm) 29-1/4" (743mm) 28-3/4" 26-1/2" (673mm) (730mm) (203mm) 14-1/4" FRAMING REQ'D WHEN OPTIONAL AP99 ACCESS PANEL IS USED

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

FINISHED FLOOR

(362mm)