29 136
GROHTHERM® SMARTCONTROL

SINGLE FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

Pure Freude an Wasser

GROHE

STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SmartControl®: push for ON-OFF, turn for volume adjustment from EcoJoy™ to Full Flow, exchangeable symbols
- GROHE TurboStat® compact ¾" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- 6 ¼" Metal wall escutcheon with GROHE QuickFix®
- ⅜" Thin profile escutcheon
- Wall plate is angle adjustable up to 6°
- Optional flow reducer for CALGreen compliance included
- Built-in check valve with dirt strainer
- Includes icons to customize push buttons: Hand Shower, Showerhead & Bath Filler
- Includes service stops
- Maximum flow performance: 7.7gpm (29L/min) @ 43.5psi (3 bar)
- Requires Grohtherm® Rapido® SmartBox (35 601) (sold separately)

PRODUCT FEATURES:

- **Speed Clean®**
- **GROHE TurboStat®**
- **GROHE QuickFix®**
- **GROHE StarLight®**

CERTIFICATIONS:

- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

29136000		GROHE StarLight® Chrome
291362430		Matte Black
29136A00		Hard Graphite
29136EN0		Brushed Nickel InfinityFinish™
29136GN0		Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 06-03-2022

PART OF LIXIL

29 136
GROHTHERM® SMARTCONTROL
SINGLE FUNCTION THERMOSTATIC
VALVE TRIM WITH CONTROL MODULE

Pure Freude an Wasser

GROHE

TECHNICAL DATA:

Product Height	**6-1/4 in**
Product Length	**1-11/16 in**
Product Width	**6-1/4 in**

Ø6 1/4"
(Ø158)

3/8"
(10)

1 11/16"
(43)