

CODE NUMBER

3910503

DESCRIPTION

6.5 gpf, Polished Chrome Finish, Single Flush, Sanigard®, Front of Valve Handle, Left of Valve Inlet, Royal® Exposed Manual Service Sink Flushometer.

DETAILS

Flush Volume: 6.5 gpf (24.6 Lpf)Finish: Polished Chrome (CP)

· Valve: Diaphragm

• Valve Body Material: Semi-red Brass

Fixture Type: Service Sink
Fixture Connection: Top spud
Rough-In Dimension: 24" (610mm)
Spud Coupling: 1 ½" (38mm)

• Supply Pipe: 1" (25mm)

• Handle: Sanigard®, Front of Valve (SG-H)

• Inlet: Left of Valve (C)

FEATURES

- Standard flush volume is 6.5 gpf /24.6 Lpf
- Flushometers may be ordered with a handle at the front or a pushbutton actuator
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.



COMPLIANCES & CERTIFICATIONS





(ADA Compliant, BAA Compliant)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi- Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

VALVE OPERATING PRESSURE (FLOWING)

15-80 PSI (103-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- Royal Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Flushometers Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the ROYAL 117 product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.



ROUGH-IN

